

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 October 2004 (21.10.2004)

PCT

(10) International Publication Number  
**WO 2004/089198 A2**

(51) International Patent Classification<sup>7</sup>: **A61B 3/00**

(21) International Application Number:  
PCT/CA2004/000537

(22) International Filing Date: 8 April 2004 (08.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/461,833 11 April 2003 (11.04.2003) US

(71) Applicant (for all designated States except US):  
**PORTABLE OPHTHALMIC DEVICES, INC.**  
[CA/US]; 4374 State Street, Unit 1A, Bettendorf, IA  
52722 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **PHILLIPS, Scott**  
[CA/CA]; 2050 Lorne Terrace, Victoria, British Colum-  
bia V8S 2H8 (CA). **HANSEN, Bjarne** [CA/CA]; 1000 De  
Costa Place, Victoria, British Columbia V8T 5H8 (CA).  
**EHRECKE, Timothy** [US/US]; 4413 Winston Place, Bet-  
tendorf, IA 52722-7202 (US).

(74) Agents: **MANNING, Gavin et al.**; 480 - 601 West Cor-  
dova Street, Vancouver, British Columbia V6B 1G1 (CA).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: PACHYMETER



(57) Abstract: A pachymeter apparatus for measuring corneal thickness is configured for the calculation of intraocular pressure ("IOP"). The apparatus includes a pachymeter for measuring corneal thickness as well as a microprocessor and a user interface. A reading of IOP from a tonometer can be entered into the device and corrected according to the pachymeter reading of corneal thickness. Correction algorithms are user selectable and user customizable. A pachymeter may have a graphical display which displays multiple locations at which measurements are to be taken. A pachymeter may use a capacitor charged by a variable current supply to measure times for signals to be reflected from a back side of a cornea.



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *without international search report and to be republished upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*